

Model Name:

Cloud POM PDU

Cloud POM PDU provides remote manual control of the critical devices by clicking on a few buttons on the smart phone or computer webpage. Stop the problem device by cutting off the power to a specific outlet. By cycling the power off and restarting the device remotely, you save time and money by eliminating the need to send technicians to the root cause of the problem.

Managers can monitor the power usage information of each output port from the remote end through the Internet to fully understand the power consumption of all the devices. Set up overload event alerts and notify managers via Email and TRAP, allowing managers to respond to crises in the shortest possible time to minimize disasters.

The PDU has two environmental sensor ports that track climate information: temperature and humidity environment variables. The data is available from any web browser and is SNMP-compliant for easy tracking of critical data without the use of any external software.

Provide central management software, which can manage a large number of PDUs' power, temperature and humidity information. The database stores the power consumption information of the power strip and provides the history curve chart for the manager's reference.

Features:

System Function:

- Built-in embedded system:
Support 10/100M Ethernet interface, provides webpage and SNMP remote management.
- Local display information:
Seven-segments can display current, web site and temperature and humidity values.
- Multiple protocols:
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, FTP, NTP, SNMP v1/2/3, TLS1.2, IPv4 and IPv6, Telnet, SSHv2
- Management Account Certification:
Radius certification support.
- Multi-account management:
Multi-group account management system. And provide three-tier permission management.
- IP filtering:
Support IP filtering, improve network security mechanisms.
- Power record:
Store up to 5000 power and event data.
- Remote firmware upgrade:
Provides remote firmware upgrade mechanism.
- System operation message:
Send the normal operation of the message automatically by trap.
- Hardware key definition:
User-definable button function.
- Temperature unit conversion:
Temperature units can choose Celsius or Fahrenheit
- System configuration restore:
Support the output of the system settings, to easily deploy a large amount of the same model of PDU.
- Multilingual Support:
Support Chinese, English, French, German, Spanish, Russian, Czech, Arabian, Persian.

Power Management:



Remote Monitor

Remote monitoring PDU status by web and SNMP



Current Measurement

Measure PDU total current consumption.



Threshold Sensing

User-definable warning and overload threshold value as the basis for alarm.



Power Sequence

User-definable power on/off sequence time.



Ping Event Control

When the specified IT device does not respond to PING, the output will perform a preset power action.



Group Control

Set multiple outlets as a single group while controlling the power output.



Event Reaction

Outlet action via pre-set event, including power, environment event and receiving trap from other device.



Environment Detection

Optional accessory probe to detect temperature and humidity.



Remote Control

Remote per outlet on/off by web and SNMP.



Mail Notification

Notify specified user by mail and SNMP when outlet action or current over threshold.



Event Alert

When current exceeds the preset threshold, PDU will beep and LED will flash.



Schedule Control

Timed & scheduled on/off/reboot control.



Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.



Outlet-Level Monitor

Remote per outlet current monitoring.



kWh Measurement

Voltage, frequency, power factor, active power, apparent power and kWh measurement.



Central Management

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.

Model Number:

WHA-3223C-24ND

Plug



Specification

Output		Input	
Voltage	200-240 VAC	Voltage	200-240 VAC
Max. Current	32 A	Frequency	50/60Hz, full range
Outlet	(21) IEC320 C13 (3) IEC320 C19	Max. Capacity	7360 VA
		Connection	IEC309, power cord, 3m
		Overload Protection	(3)16A circuit breaker (UL489)
Measurement		Other	
Current	+/-1%+/-0.1A @0.2A ~ 20 A	ENV Connection	(2) RJ11
Voltage	+/- 1% +/- 1V @80V~260V		
Active Power	+/- 1% +/- 5W @50W~8000W		
Apparent Power	+/- 1% @50VA~8000VA		
Frequency	+/- 1% @50~65Hz		
Power Factor	+/- 1% @0.1~1.0		
kWh	.001kWh~99999.999kWh, (+/- 1% @50W~8000W) kh=1.0		
Dimension/Weight		Operation	
Net Size	1778 x 56 x 80 mm	Operation Temp.	0 ~ 45°C
Net Weight	7.8 kg	Operation Humid.	0% ~ 90% RH
Package Size	1890 x 220 x 110 mm	Storage Temp.	-20°C ~ 65°C
Package Weight	9.0 kg	Storage Humid.	0% ~ 90% RH
Approval			
Certification	CE, FCC, UL		
Warranty	2 years		

Package

No.	Description
1	PDU 1 set
2	Rack mount accessories 1 set
3	Software CD (manual, MIB)

Accessory

Model Number	Model Name
CPM-ENV-2	Temp./Humidity probe (ENV)
STR-C14-B	C13 socket protection
STR-C20-B	C19 socket protection



Line Drawing

