

15Amp 115V

Model Name

Switched PDU

Model Number

SWB-1511A-08N1



Meter True RMS Current Meter

Power Monitor Total Current Monitoring by Meter, Web, SNMP and Central Software

Protocols Http, IPv4/v6
SNMPv1/v3, DHCP, UDP, SSH, SSLv3, TLS1.0, TLS1.1, TLS1.2

Outlet Control Individual, Group, Schedule, Auto Ping, Trap Events

Power Delay Power On/Off Sequence can be Defined

Alarm Thresholds User-Defined for Warning and Overload

Event Alert Email, Trap, Audible

Store events and data records

Temp./Humidity Option Accessory

General

Output	(8) NEMA 5-15/20R (1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5-15P Power Cord 3 Meters long
Input	
Output Protection	(1) 15 AMP Circuit Breaker

Communication

SSL Indication	(1) Blue LED
DHCP Indication	(1) Green LED
Circuit Threshold	(1) Red LED
Outlet On/Off	(8) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(2) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

Power Information

Current	Range: 0A ~ 32 A Resolution: 0.1A Precision: +/-2%+/-0.1AMP
---------	---

Operation

Nominal Voltage	115V
On-Line Voltage	100V~ 127V
Frequency	50/60Hz
Max. Output Current	15 Amp
Operation Temp.	0 ~ 45 Celsius degree
Humidity	0% ~ 90%
Size	215 x 432 x 44.45 mm
Net Weight	3.5 kg
Regulatory Approvals	UL 60950-1, UL Listed, CSA, cUL Listed, CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3 FCC Part 15 Class A, ICES-003

