

15Amp 115V

Model Name
POM / kWh PDU

Model Number
WHB-1511A-08N8



Meter True RMS Current Meter, Voltage, Frequency, Power Factor, Active Power, Apparent Power, Total kWh, Sub-total kWh.

Power Monitor Per Outlet Output Current and Total Power Monitoring by Meter, Web, SNMP, Free Bundle Software

Protocols Http, Https, IPv4/v6 SNMPv1/v3, DHCP, UDP, SSH, SSLv3, TLS1.0, TLS1.1, TLS1.2

Outlet Control Individual, Group, Schedule, Auto Ping, Trap Events

Power Delay Power On/Off Sequence can be Defined

Alarm Thresholds User-Defined for Warning and Overload

Event Alert Email, Trap, Audible

Store events and data records

Temp./Humidity Option Accessory

General

Output	(8) NEMA 5-15/20R
Input	(1) IEC320 C20 Inlet; Enclosed IEC320 C19 to NEMA 5-15P Power Cord 3 Meters long
Output Protection	(1) 15 AMP Circuit Breaker

Communication

SSL Indication	(1) Blue LED
DHCP Indication	(1) Green LED
Circuit Threshold	(1) Red LED
Outlet Threshold	(8) Red LED
Outlet On/Off	(8) Green LED
Network	(1) RJ45 for Ethernet
Temp./Humidity	(2) RJ11 for ENV probe connection
Identification	1 Digits Seven Segments for Identification
Meter	3 Digits Seven Segments

Power Information

Voltage	+/- 1% @ 80V~260V
Active Power	+/- 1% @ 50W~8000W
Apparent Power	+/- 1% @ 50VA~8000VA
Frequency	+/- 1% @ 50~65Hz
Power Factor	+/- 1% @ 0.1~1.0
kWh	Range: 0.001kWh ~ 99999.999kWh Precision: +/-1% @ 50W~8000W, kh=1.0
Current	Range: 0A ~ 32 A Resolution: 0.1A Precision: +/-1%/+/-0.1AMP

Operation

Nominal Voltage	115V
On-Line Voltage	100V~ 127V
Frequency	50/60Hz
Max. Output Current	15 Amp
Operation Temp.	0 ~ 45 Celsius degree
Humidity	0% ~ 90%
Size	215 x 432 x 44.45 mm
Net Weight	3.6 kg
Regulatory Approvals	UL 60950-1, UL Listed, CSA, cUL Listed, CE, EN 55032 Class A, EN 55024, EN 61000-3-2, EN 61000-3-3, FCC Part 15 Class A, ICES-003

